JOB: _____

CONTRACTOR: _____

P.O. NO. _____

V.E. DWG. NO. _____

DOUBLE SPHERE FLEXIBLE CONNECTORS WITH FLOATING FLANGES



NOTES:

1. THIS FLEXIBLE JOINT SHOULD BE INSTALLED THE LENGTH SHOWN ON DRAWING. PIPING AND EQUIPMENT CONNECTED BY THIS FLEXIBLE JOINT MUST BE PROPERLY ANCHORED AND OR GUIDED.
2. NOT INTENDED FOR TORSION.
3. NOT INTENDED FOR USE WITH VICTAULIC FLANGE.

TO BE FURNISHED WITH CONTROL RODS YES ☐ NO ☐

QTY. (PCS.)	JOINT SIZE I.D. (IN.)	FACE TO FACE (IN.)	PRESSURE (PSI) vs. TEMPERATURE			MOVEMENT CAPABILITY				TAG
			170°F	200°F	220°F	COMPRESSION (IN.)	ELONGATION (IN.)	LATERAL (IN.)	ANGULAR (DEGREES)	
	2	7	225	190	150	2	1 3/16	1 3/4	45	
	2 1/2	7	225	190	150	2	1 3/16	1 3/4	43	
	3	7	225	190	150	2	1 3/16	1 3/4	38	
	4	9	225	190	150	2	1 3/8	1 9/16	34	
	5	9	225	190	150	2	1 3/8	1 9/16	29	
	6	9	225	190	150	2	1 3/8	1 9/16	25	
	8	13	225	190	150	2 3/8	1 3/8	1 3/8	19	
	10	13	225	190	150	2 3/8	1 3/8	1 3/8	15	
	12	13	225	190	150	2 3/8	1 3/8	1 3/8	13	
	14	13 3/4	150	125	100	1 3/4	1 3/16	1 3/16	9	

VIBRATION ELIMINATOR CO., INC. ■ 15 Dixon Avenue ■ Copiague, New York 11726
Tel. (631)841-4000 Fax (631)841-0020